

## SPECIFICATIONS

# PCIe-5764

## 16-Bit, 1 GS/s, 4-Channel PCI FlexRIO Digitizer Device

This document lists the specifications for the PCIe-5764. Specifications are subject to change without notice. For the most recent device specifications, refer to [ni.com/support](http://ni.com/support).



**Note** These specifications are typical at 25 °C unless otherwise noted.

## Contents

---

Definitions.....	1
Digital I/O.....	2
Digital I/O Single-Ended Channels.....	2
Digital I/O High-Speed Serial MGT.....	3
Reconfigurable FPGA.....	3
Onboard DRAM.....	4
Analog Input.....	5
General Characteristics.....	5
Typical Specifications.....	5
REF/CLK IN.....	13
General Characteristics.....	13
Bus Interface.....	16
Maximum Power Requirements.....	16
Physical.....	17
Environment.....	17
Operating Environment.....	17
Storage Environment.....	17

## Definitions

---

*Warranted* specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

*Characteristics* describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- *Typical* specifications describe the performance met by a majority of models.
- *Nominal* specifications describe an attribute that is based on design, conformance testing, or supplemental testing.
- *Measured* specifications describe the measured performance of a representative model.

Specifications are *Typical* unless otherwise noted.

## Digital I/O

Connector	Molex™ Nano-Pitch I/O™
5.0 V Power	±5%, 50 mA maximum, nominal

**Table 1.** Digital I/O Signal Characteristics

Signal	Type	Direction
MGT Tx± <3..0> <sup>1</sup>	Xilinx UltraScale GTH	Output
MGT Rx± <3..0> <sup>1</sup>	Xilinx UltraScale GTH	Input
DIO <7..0>	Single-ended	Bidirectional
5.0 V	DC	Output
GND	Ground	—

## Digital I/O Single-Ended Channels

Number of channels	8
Signal type	Single-ended
Voltage families	3.3 V, 2.5 V, 1.8 V, 1.5 V, 1.2 V
Input impedance	100 kΩ, nominal
Output impedance	50 Ω, nominal
Direction control	Per channel
Minimum required direction change latency	200 ns
Maximum output toggle rate	60 MHz with 100 μA load, nominal

**Table 2.** Digital I/O Single-Ended DC Signal Characteristics<sup>2</sup>

Voltage Family	V <sub>IL</sub>	V <sub>IH</sub>	V <sub>OL</sub> (100μA load)	V <sub>OH</sub> (100μA load)	Maximum DC Drive Strength
3.3 V	0.8 V	2.0 V	0.2 V	3.0 V	24 mA
2.5 V	0.7 V	1.6 V	0.2 V	2.2 V	18 mA

<sup>1</sup> Multi-gigabit transceiver (MGT) signals are available on devices with KU040 and KU060 FPGAs only.

<sup>2</sup> Voltage levels are guaranteed by design through the digital buffer specifications.

**Table 2.** Digital I/O Single-Ended DC Signal Characteristics<sup>2</sup> (Continued)

Voltage Family	V <sub>IL</sub>	V <sub>IH</sub>	V <sub>OL</sub> (100µA load)	V <sub>OH</sub> (100µA load)	Maximum DC Drive Strength
1.8 V	0.62 V	1.29 V	0.2 V	1.5 V	16 mA
1.5 V	0.51 V	1.07 V	0.2 V	1.2 V	12 mA
1.2 V	0.42 V	0.87 V	0.2 V	0.9 V	6 mA

## Digital I/O High-Speed Serial MGT<sup>3</sup>



**Note** MGTs are available on devices with KU040 and KU060 FPGAs only.

Data rate	500 Mbps to 16.375 Gbps, nominal
Number of Tx channels	4
Number of Rx channels	4
I/O AC coupling capacitor	100 nF

### MGT TX± Channels

Minimum differential output voltage <sup>4</sup>	170 mV pk-pk into 100 Ω, nominal
I/O coupling	AC-coupled with 100 nF capacitor

### MGT RX± Channels

Differential input voltage range	
≤ 6.6 Gb/s	150 mV pk-pk to 2000 mV pk-pk, nominal
> 6.6 Gb/s	150 mV pk-pk to 1250 mV pk-pk, nominal
Differential input resistance	100 Ω, nominal
I/O coupling	DC-coupled, requires external capacitor △

## Reconfigurable FPGA

PCIe-5764 modules are available with multiple FPGA options. The following table lists the FPGA specifications for the PCIe-5764 FPGA options.

<sup>2</sup> Voltage levels are guaranteed by design through the digital buffer specifications.

<sup>3</sup> For detailed FPGA and High-Speed Serial Link specifications, refer to Xilinx documentation.

<sup>4</sup> 800 mV pk-pk when transmitter output swing is set to the maximum setting.

**Table 3. Reconfigurable FPGA Options**

	<b>KU035</b>	<b>KU040</b>	<b>KU060</b>
LUTs	203,128	242,200	331,680
DSP48 slices (25 × 18 multiplier)	1,700	1,920	2,760
Embedded Block RAM	19.0 Mb	21.1 Mb	38.0 Mb
Default timebase	80 MHz		
Timebase reference sources	Onboard 100 MHz oscillator		
Data transfers	DMA, interrupts, programmed I/O	DMA, interrupts, programmed I/O, multi-gigabit transceivers	
Number of DMA channels	60		



**Note** The Reconfigurable FPGA Options table depicts the total number of FPGA resources available on the part. The number of resources available to the user is slightly lower, as some FPGA resources are consumed by board-interfacing IP for PCI Express, device configuration, and various board I/O. For more information, contact NI support.



**Note** For FPGA designs using the majority of KU040 or KU060 FPGA resources while running at clock rates over 150 MHz, the module may require more power than is available. If the module attempts to draw more than allowed per its specification, the module protects itself and reverts to a default FPGA personality. Refer to the getting started guide for your module or contact NI support for more information.

## Onboard DRAM

Memory size	4 GB (2 banks of 2 GB)
DRAM clock rate	1064 MHz
Physical bus width	32 bit
LabVIEW FPGA DRAM clock rate	267 MHz
LabVIEW FPGA DRAM bus width	256 bit per bank
Maximum theoretical data rate	17 GB/s (8.5 GB/s per bank)

# Analog Input

---



**Notice** The maximum input signal levels are valid only when the module is powered on. To avoid permanent damage to the PCIe-5764, do not apply a signal to the device when the module is powered down.

## General Characteristics

Number of channels	4, single-ended, simultaneously sampled
Connector type	SMA
Input impedance	50 $\Omega$
Input coupling	AC or DC <sup>5</sup>
Sample rate	
Internal Sample Clock	1 GHz
External Sample Clock	1 GHz
Analog-to-digital converter (ADC)	ADS54J60, 16-bit resolution

## Typical Specifications

### Full-scale input range (normal operating conditions)

AC-coupled	2.05 $V_{pp}$ (10.22 dBm) at 10 MHz
DC-coupled	2.00 $V_{pp}$ (10 dBm)

### Gain accuracy

AC-coupled	$\pm 0.1$ dB at 10 MHz
DC-coupled	$\pm 0.79\%$ at DC

### DC offset

AC-coupled	$\pm 22$ $\mu V$
DC-coupled	$\pm 363$ $\mu V$

### Bandwidth (-3 dB)<sup>6</sup>

AC-coupled	0.07 MHz to 1.15 GHz <sup>7</sup>
DC-coupled	DC to 400 MHz

---

<sup>5</sup> Only one analog input path type is populated.

<sup>6</sup> Normalized to 10 MHz.

<sup>7</sup> Maximum bandwidth for full scale input signal is 400 MHz. See the ADS54J60 datasheet for details on maximum supported amplitude for frequencies greater than 400 MHz.

**Table 4.** Single Tone Spectral Performance

	AC-Coupled			DC-Coupled		
	Input Frequency			Input Frequency		
	10.1 MHz	123.1 MHz	199.1 MHz	10.1 MHz	123.1 MHz	199.1 MHz
SNR <sup>8</sup> (dBFS)	69.8	68.7	67	68.7	67.5	65.8
SINAD <sup>8</sup> (dBFS)	68.7	67.6	66.7	68.1	67.1	65.3
SFDR (dBc)	-80.7	-81.8	-75.6	-76.6	-75.8	-73.4
ENOB <sup>9</sup> (Bits)	11.1	10.9	10.8	11.0	10.9	10.6



**Note** Excludes ADC interleaving spurs.

**Table 5.** Noise Spectral Density

Module	nV/rt (Hz)	dBm/Hz	dBFS/Hz
AC-coupled	9.7	-147.3	-157.5
DC-coupled	11.9	-145.5	-155.5




**Note** Noise spectral density is verified using a 50  $\Omega$  terminator connected to the input.


<sup>8</sup> Measured with a -1 dBFS signal and corrected to full-scale. 1 kHz resolution bandwidth.

<sup>9</sup> Calculated from SINAD and corrected to full-scale.


**Figure 1. AC-Coupled Single Tone Spectrum (10.1 MHz, -1 dBFS, 1 kHz RBW), Measured**




**Figure 2. AC-Coupled Single Tone Spectrum (123.1 MHz, -1 dBFS, 1 kHz RBW), Measured**




**Figure 3. AC-Coupled Single Tone Spectrum (199.1 MHz, -1 dBFS, 1 kHz RBW), Measured**




**Figure 4. DC-Coupled Single Tone Spectrum (10.1 MHz, -1 dBFS, 1 kHz RBW), Measured**



**Figure 5.** DC-Coupled Single Tone Spectrum (123.1 MHz, -1 dBFS, 1 kHz RBW), Measured



**Figure 6. DC-Coupled Single Tone Spectrum (199.1 MHz, -1 dBFS, 1 kHz RBW), Measured**




Channel-to-channel crosstalk AC-coupled, measured

1 MHz	-87 dB
100 MHz	-90 dB
250 MHz	-85 dB
400 MHz	-84 dB


Channel-to-channel crosstalk DC-coupled, measured

1 MHz	-88 dB
100 MHz	-84 dB
250 MHz	-75 dB
400 MHz	-75 dB


**Figure 7. AC-Coupled Frequency Response, Measured**




**Figure 8. AC-Coupled Passband Flatness for Full Scale Input Supported Frequency Range, Measured**




**Figure 9. DC-Coupled Frequency Response, Measured**



**Figure 10. DC-Coupled Frequency Response Zoomed In, Measured**



**Figure 11. Input Return Loss, Measured**



## REF/CLK IN

### General Characteristics

Connector type	SMA
Input impedance	50 $\Omega$
Input coupling	AC
Reference input voltage range	0.3 V <sub>pp</sub> to 4 V <sub>pp</sub>
Sample Clock input voltage range	0.3 V <sub>pp</sub> to 4 V <sub>pp</sub>
Absolute maximum voltage	$\pm 12$ V DC, 4 V <sub>pp</sub> AC
Duty cycle	45% to 55%
Onboard reference timebase stability	$\pm 0.5$ ppm
Sample Clock jitter <sup>10</sup>	
AC-coupled	140 fs RMS
DC-coupled	143 fs RMS

<sup>10</sup> Integrated from 1 kHz to 10 MHz. Includes the effects of the converter aperture uncertainty and the clock circuitry jitter. Excludes trigger jitter.


**Table 6. Clock Configuration Options**

<b>Clock Configuration</b>	<b>External Clock Type</b>	<b>External Clock Frequency</b>	<b>Description</b>
Internal Reference Clock <sup>11</sup>	—	—	The internal Sample Clock locks to an onboard voltage-controlled temperature compensated crystal oscillator (VCTCXO).
Internal Baseboard Reference Clock	—	10 MHz	The internal Sample Clock locks to the 10 MHz Reference Clock provided from the FPGA baseboard.
External Reference Clock (REF/CLK IN)	Reference Clock	10 MHz <sup>12</sup>	The internal Sample Clock locks to an external Reference Clock, which is provided through the REF/CLK IN front panel connector.
External Sample Clock (REF/CLK IN)	Sample Clock	1 GHz	An external Sample Clock can be provided through the REF/CLK IN front panel connector.


<sup>11</sup> Default clock configuration.

<sup>12</sup> The PLL Reference Clock must be accurate to  $\pm 25$  ppm.

**Figure 12. AC-Coupled Phase Noise with 385.6 MHz Input Tone, Measured**



**Figure 13. DC-Coupled Phase Noise with 385.6 MHz Input Tone, Measured**



## Bus Interface

Card edge form factor	PCI Express Gen-3 x8
Slot compatibility	x8 and x16 PCI Express

## Maximum Power Requirements



**Note** Power requirements are dependent on the contents of the LabVIEW FPGA VI used in your application.

+3.3 V	4.5 A
+12 V	5 A
Maximum total power	75 W

# Physical

---

Dimensions (including I/O bracket, not including connectors)	12.6 cm × 26.3 cm × 4 cm (5.0 in. × 10.4 in. × 1.6 in.)
Weight	990 g (35 oz)
PCI Express mechanical form factor	Standard height, three-quarter length, double slot
Integrated air mover (fan)	Yes
Maximum rear panel exhaust airflow	84 m <sup>3</sup> /h (50 CFM) (without any chassis impedance)

---

# Environment

---

Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

---

Indoor use only.

# Operating Environment

Operating temperature, local <sup>13</sup>	0 °C to 45 °C
Operating humidity	10% to 90% RH, noncondensing

---

# Storage Environment

Ambient temperature range	-20 °C to 70 °C
Relative humidity range	5% to 95% RH, noncondensing

---

---

<sup>13</sup> For PCI Express adapter cards with integrated air movers, NI defines the local operational ambient environment to be at the fan inlet. For cards without integrated air movers, NI defines the local operational ambient environment to be 25 mm (1 in.) upstream of the leading edge of the card.

Information is subject to change without notice. Refer to the *NI Trademarks and Logo Guidelines* at [ni.com/trademarks](http://ni.com/trademarks) for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at [ni.com/patents](http://ni.com/patents). You can find information about end-user license agreements (EULAs) and third-party legal notices in the `readme` file for your NI product. Refer to the *Export Compliance Information* at [ni.com/legal/export-compliance](http://ni.com/legal/export-compliance) for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2019—2020 National Instruments. All rights reserved.

377967B-01 January 28, 2020