

标题	产品编码	含税价格	Dia. (mm)	EFL (mm)	NA	BFL (mm)	CT (mm)	涂层	涂层规格	基底	CA (mm)	非球面图形误差 (µm RMS)	表面质量	ET (mm)	中心偏 (弧分)	倒角	有效焦距/有效孔径直径比	Shape of Back Surface	波长范围 (nm)	Conjugate Distance	RoHS 2015	Reach 219	RoHS
10mm Dia., 0.63 NA, Uncoated, NIR Precision Aspheric Lens	13-496	RMB 1269.84	10.00+0.00/-0.10	8.00 @ 780nm	0.63	5.92	3.70 ±0.10	Uncoated		S-LAH64	9	0.75	40-20	1.57	<3	Protective bevel as needed	0.80	Plano	375 - 2100	Infinite	符合标准	符合标准	
10mm Dia., 0.63 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-266	RMB 1433.69	10.00+0.00/-0.10	8.00 @ 780nm	0.63	5.92	3.70 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	9	0.75	40-20	1.57	<3	Protective bevel as needed	0.80	Plano	350 - 700	Infinite			符合标准
10mm Dia., 0.63 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-278	RMB 1433.69	10.00+0.00/-0.10	8.00 @ 780nm	0.63	5.92	3.70 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	9	0.75	40-20	1.57	<3	Protective bevel as needed	0.80	Plano	600 - 1050	Infinite			符合标准
10mm Dia., 0.63 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-290	RMB 1433.69	10.00+0.00/-0.10	8.00 @ 780nm	0.63	5.92	3.70 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	9	0.75	40-20	1.57	<3	Protective bevel as needed	0.80	Plano	900 - 1700	Infinite			符合标准
12.5mm Dia., 0.25 NA, Uncoated, NIR Precision Aspheric Lens	13-498	RMB 1433.69	12.50+0.00/-0.10	25.00 @ 780nm	0.25	22.35	4.00 ±0.10	Uncoated		N-BK7	11.25	0.75	40-20	2.43	<3	Protective bevel as needed	2.00	Plano	350 - 2200	Infinite	符合标准	符合标准	
12.5mm Dia., 0.25 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-268	RMB 1597.54	12.50+0.00/-0.10	25.00 @ 780nm	0.25	22.35	4.00 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	N-BK7	11.25	0.75	40-20	2.43	<3	Protective bevel as needed	2.00	Plano	350 - 700	Infinite			符合标准
12.5mm Dia., 0.25 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-280	RMB 1597.54	12.50+0.00/-0.10	25.00 @ 780nm	0.25	22.35	4.00 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	N-BK7	11.25	0.75	40-20	2.43	<3	Protective bevel as needed	2.00	Plano	600 - 1050	Infinite			符合标准
12.5mm Dia., 0.25 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-292	RMB 1597.54	12.50+0.00/-0.10	25.00 @ 780nm	0.25	22.35	4.00 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	N-BK7	11.25	0.75	40-20	2.43	<3	Protective bevel as needed	2.00	Plano	900 - 1700	Infinite			符合标准
12.5mm Dia., 0.63 NA, Uncoated, NIR Precision Aspheric Lens	13-497	RMB 1433.69	12.50+0.00/-0.10	10.00 @ 780nm	0.63	7.61	4.25 ±0.10	Uncoated		S-LAH64	11.25	0.75	40-20	1.60	<3	Protective bevel as needed	0.80	Plano	375 - 2100	Infinite	符合标准	符合标准	
12.5mm Dia., 0.63 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-267	RMB 1597.54	12.50+0.00/-0.10	10.00 @ 780nm	0.63	7.61	4.25 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	11.25	0.75	40-20	1.60	<3	Protective bevel as needed	0.80	Plano	350 - 700	Infinite			符合标准
12.5mm Dia., 0.63 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-279	RMB 1597.54	12.50+0.00/-0.10	10.00 @ 780nm	0.63	7.61	4.25 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	11.25	0.75	40-20	1.60	<3	Protective bevel as needed	0.80	Plano	600 - 1050	Infinite			符合标准
12.5mm Dia., 0.63 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-291	RMB 1597.54	12.50+0.00/-0.10	10.00 @ 780nm	0.63	7.61	4.25 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	11.25	0.75	40-20	1.60	<3	Protective bevel as needed	0.80	Plano	900 - 1700	Infinite			符合标准
15mm Dia., 0.63 NA, Uncoated, NIR Precision Aspheric Lens	13-499	RMB 2416.79	15.00+0.00/-0.10	12.00 @ 780nm	0.63	9.02	5.28 ±0.10	Uncoated		S-LAH64	13.5	0.75	40-20	2.09	<3	Protective bevel as needed	0.80	Plano	375 - 2100	Infinite	符合标准	符合标准	
15mm Dia., 0.63 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-269	RMB 2580.64	15.00+0.00/-0.10	12.00 @ 780nm	0.63	9.02	5.28 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	13.5	0.75	40-20	2.09	<3	Protective bevel as needed	0.80	Plano	350 - 700	Infinite			符合标准
15mm Dia., 0.63 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-281	RMB 2580.64	15.00+0.00/-0.10	12.00 @ 780nm	0.63	9.02	5.28 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	13.5	0.75	40-20	2.09	<3	Protective bevel as needed	0.80	Plano	600 - 1050	Infinite			符合标准
15mm Dia., 0.63 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-293	RMB 2580.64	15.00+0.00/-0.10	12.00 @ 780nm	0.63	9.02	5.28 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	13.5	0.75	40-20	2.09	<3	Protective bevel as needed	0.80	Plano	900 - 1700	Infinite			符合标准
18mm Dia., 0.60 NA, Uncoated, NIR Precision Aspheric Lens	13-500	RMB 2539.68	18.00+0.00/-0.10	15.00 @ 780nm	0.60	11.51	6.20 ±0.10	Uncoated		S-LAH64	16.2	0.75	40-20	2.55	<3	Protective bevel as needed	0.83	Plano	375 - 2100	Infinite	符合标准	符合标准	
18mm Dia., 0.60 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-270	RMB 2703.53	18.00+0.00/-0.10	15.00 @ 780nm	0.60	11.51	6.20 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	16.2	0.75	40-20	2.55	<3	Protective bevel as needed	0.83	Plano	350 - 700	Infinite			符合标准
18mm Dia., 0.60 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-282	RMB 2703.53	18.00+0.00/-0.10	15.00 @ 780nm	0.60	11.51	6.20 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	16.2	0.75	40-20	2.55	<3	Protective bevel as needed	0.83	Plano	600 - 1050	Infinite			符合标准
18mm Dia., 0.60 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-294	RMB 2703.53	18.00+0.00/-0.10	15.00 @ 780nm	0.60	11.51	6.20 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	16.2	0.75	40-20	2.55	<3	Protective bevel as needed	0.83	Plano	900 - 1700	Infinite			符合标准
20mm Dia., 0.56 NA, Uncoated, NIR Precision Aspheric Lens	13-501	RMB 2580.64	20.00+0.00/-0.10	17.99 @ 780nm	0.56	14.00	7.10 ±0.10	Uncoated		S-LAH64	18	0.75	40-20	3.37	<3	Protective bevel as needed	0.90	Plano	375 - 2100	Infinite	符合标准	符合标准	
20mm Dia., 0.56 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-271	RMB 2744.49	20.00+0.00/-0.10	17.99 @ 780nm	0.56	14.00	7.10 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	18	0.75	40-20	3.37	<3	Protective bevel as needed	0.90	Plano	350 - 700	Infinite			符合标准
20mm Dia., 0.56 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-283	RMB 2744.49	20.00+0.00/-0.10	17.99 @ 780nm	0.56	14.00	7.10 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	18	0.75	40-20	3.37	<3	Protective bevel as needed	0.90	Plano	600 - 1050	Infinite			符合标准
20mm Dia., 0.56 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-295	RMB 2744.49	20.00+0.00/-0.10	17.99 @ 780nm	0.56	14.00	7.10 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	18	0.75	40-20	3.37	<3	Protective bevel as needed	0.90	Plano	900 - 1700	Infinite			符合标准
25mm Dia., 0.25 NA, Uncoated, NIR Precision Aspheric Lens	13-503	RMB 1884.28	25.00+0.00/-0.10	50.00 @ 780nm	0.25	46.03	6.00 ±0.10	Uncoated		N-BK7	22.5	0.75	40-20	2.86	<3	Protective bevel as needed	2.00	Plano	350 - 2200	Infinite	符合标准	符合标准	
25mm Dia., 0.25 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-273	RMB 2130.05	25.00+0.00/-0.10	50.00 @ 780nm	0.25	46.03	6.00 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	N-BK7	22.5	0.75	40-20	2.86	<3	Protective bevel as needed	2.00	Plano	350 - 700	Infinite			符合标准
25mm Dia., 0.25 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-285	RMB 2130.05	25.00+0.00/-0.10	50.00 @ 780nm	0.25	46.03	6.00 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	N-BK7	22.5	0.75	40-20	2.86	<3	Protective bevel as needed	2.00	Plano	600 - 1050	Infinite			符合标准
25mm Dia., 0.25 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-297	RMB 2130.05	25.00+0.00/-0.10	50.00 @ 780nm	0.25	46.03	6.00 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	N-BK7	22.5	0.75	40-20	2.86	<3	Protective bevel as needed	2.00	Plano	900 - 1700	Infinite			符合标准
25mm Dia., 0.63 NA, Uncoated, NIR Precision Aspheric Lens	13-502	RMB 2867.38	25.00+0.00/-0.10	20.00 @ 780nm	0.63	15.73	7.60 ±0.10	Uncoated		S-LAH64	22.5	0.75	40-20	2.30	<3	Protective bevel as needed	0.80	Plano	375 - 2100	Infinite	符合标准	符合标准	
25mm Dia., 0.63 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-272	RMB 3113.15	25.00+0.00/-0.10	20.00 @ 780nm	0.63	15.73	7.60 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	22.5	0.75	40-20	2.30	<3	Protective bevel as needed	0.80	Plano	350 - 700	Infinite			符合标准
25mm Dia., 0.63 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-284	RMB 3113.15	25.00+0.00/-0.10	20.00 @ 780nm	0.63	15.73	7.60 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	22.5	0.75	40-20	2.30	<3	Protective bevel as needed	0.80	Plano	600 - 1050	Infinite			符合标准
25mm Dia., 0.63 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-296	RMB 3113.15	25.00+0.00/-0.10	20.00 @ 780nm	0.63	15.73	7.60 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	22.5	0.75	40-20	2.30	<3	Protective bevel as needed	0.80	Plano	900 - 1700	Infinite			符合标准
30mm Dia., 0.58 NA, Uncoated, NIR Precision Aspheric Lens	13-504	RMB 3236.04	30.00+0.00/-0.10	26.00 @ 780nm	0.58	20.57	9.65 ±0.10	Uncoated		S-LAH64	27	0.75	40-20	3.82	<3	Protective bevel as needed	0.87	Plano	375 - 2100	Infinite	符合标准	符合标准	
30mm Dia., 0.58 NA, 350-700nm Coated, NIR Precision Aspheric Lens	16-274	RMB 3481.81	30.00+0.00/-0.10	26.00 @ 780nm	0.58	20.57	9.65 ±0.10	VIS+ (350-700nm)	Ravg < 0.5% @ 350 - 700nm @ 0° ±30° AOI Rabs < 1.5% @ 350 - 700nm @ 0° ±30° AOI	S-LAH64	27	0.75	40-20	3.82	<3	Protective bevel as needed	0.87	Plano	350 - 700	Infinite			符合标准
30mm Dia., 0.58 NA, 600-1050nm Coated, NIR Precision Aspheric Lens	16-286	RMB 3481.81	30.00+0.00/-0.10	26.00 @ 780nm	0.58	20.57	9.65 ±0.10	NIR+ (600-1050nm)	Ravg < 0.5% @ 600 - 1050nm @ 0° ±30° AOI Rabs < 1.5% @ 600 - 1050nm @ 0° ±30° AOI	S-LAH64	27	0.75	40-20	3.82	<3	Protective bevel as needed	0.87	Plano	600 - 1050	Infinite			符合标准
30mm Dia., 0.58 NA, 900-1700nm Coated, NIR Precision Aspheric Lens	16-298	RMB 3481.81	30.00+0.00/-0.10	26.00 @ 780nm	0.58	20.57	9.65 ±0.10	SWIR+ (900-1700nm)	Ravg < 0.5% @ 900 - 1700nm @ 0° ±30° AOI Rabs < 1% @ 900 - 1700nm @ 0° ±30° AOI	S-LAH64	27	0.75	40-20										